



INSULATION MACHINE CORP

# Accu1 9400

## Insulation Blowing Machine



The Accu1 9400 is a portable, all fiber, blowing and spraying machine, engineered with the busy contractor in mind. The variable speed blower and adjustable material feed provide powerful, efficient operation with maximum production from a 115-volt machine. Durable construction and corrosion resistant coating provide long life with minimal maintenance.

### Production Rates

- Cellulose: 2500 lbs/hr
- Fiberglass: 900 lbs/hr
- Rockwool: 1400 lbs/hr

### Specifications

- Weight: 390 lbs
- Dimensions: 26" W x 38" D x 48" H
- Hopper Capacity: 14 cu. ft.
- Airlock: 10" L x 10" diameter
- Blower Size: Single 12.9 A / 3-stage - standard (Double Blower configuration available)
- Power requirements: Dual input, 15 amp/115V/60 Hz (230V/50Hz, CE configuration available)
- Hose: 3" diameter up to 400 feet

### Features

- Modular component design
- Welded steel construction with powder coated finish
- Hopper guards
- Recessed control panel
- 1 hp TEFC drive motor
- Material conditioning card system and Variable Speed Agitator
- Limited moving parts
- Volt-meter
- Circuit Breaker protection
- Emergency Stop
- Control Panel Override Switch

### Benefits

- Quick part replacement and routine maintenance
- Resists damage and corrosion
- Operator safety
- Avoids unintended power shut downs
- Processes the toughest blowing materials
- Optimum control of conditioning fibers
- Reduced frequency of breakdowns and downtime