



INSULATION MACHINE CORP

# Accu1 9500

## Insulation Blowing Machine



The Accu1 9500 provides the contractor with the most power and versatility in a portable, multi-story, blowing, spraying and fireproofing machine. Durable construction and corrosion resistant coating provide long life with minimal maintenance.

### Production Rates

- Cellulose: 2750 lbs/hr
- Fiberglass: 1000 lbs/hr
- Rockwool: 1550 lbs/hr

### Specifications

- Weight: 455 lbs
- Dimensions: 26" W x 38" D x 48" H
- Hopper Capacity: 14 cu. ft.
- Airlock: 10" L x 10" diameter
- Blower Size: dual, 12.9 A / 3-stage –standard
- Power requirements: Single 20A @ 240 VAC
- Hose: 3" diameter up to 500 feet
- Volt meter and hour meter included

### Features

- Modular component design
- Welded steel construction with powder coated finish
- Hopper guards
- Recessed control panel
- 1.5 hp TEFC drive motor
- Material conditioning card system and Variable Speed Agitator
- Limited moving parts

### Benefits

- Quick part replacement and routine maintenance
- Resists damage and corrosion
- Operator safety
- Avoids unintended power shut downs
- Processes the toughest blowing materials
- Optimum control of conditioning fibers
- Reduced frequency of breakdowns and downtime